



NOTES:

- 1. ALL RESISTORS IN OHMS, KW, SK.
- 2. ALL DIODES ARE IN4154.
- 3. ALL .01UF CAPACITORS ARE 25V.
- 4. ALL 1% RESISTORS ARE 1/4W.
- 5. ALL GROUNDS ARE 1/4W.
- 6. ALL FETS ARE PI037E.
- 7. THIS SCHEMATIC IS VALID FOR THE FOLLOWING ASSEMBLIES.

52/176	52/25	-00	"R"	PCN 1078
52/176	52/45	-01	"R"	PCN 1078
52/176	52/55	-02	"R"	PCN 1078
52/176	52/130	-03	"R"	PCN 1058
52/176	52/140	-04	"R"	PCN 1078
52/176	WT 40	-05	"S"	PCN 1058

② SELECTED RESISTOR

UNIT	RESISTOR
52/25 -00	R221, 1.5K, 1%
52/25 -01	R221, 1.5K, 1%
52/25 -02	R221, 1.5K, 1%
52/25 -03	R221, 1.27K, 1%
52/45 -04	R221, 1.27K, 1%
WT 40 -05	R221, 1.27K, 1%

S	1078	T	1068
P	0910	R	101
M	0828	N	0868
K	0740	L	0787
J	0710	I	0704
H	0616	G	0616
G	0616	F	0616
F	0616	E	0616
E	0616	D	0616
D	0616	C	0616
C	0616	B	0616
B	0616	A	0616

DATE	11/77
BY	J. D. [Signature]
CHKD	[Signature]
APP'D	[Signature]
NO. OF COPIES	4
NO. OF SHEETS	4
REV	D
QUME	90630-KK T