



LAST USED
C6, R19, CR6, F1,
U5

NOTES:

UNLESS OTHERWISE SPECIFIED:

1. ALL RESISTORS ARE 1/4 W, 5%.
2. RESISTOR R1, R17, R18 AND R19 ARE 1/4 W, 1%, R19 *W 5%.
3. ALL CAPACITORS ARE 0.1 MFD, 12V.
4. CAPACITOR C1, 100 MFD, 25V, CAPACITOR C6, 22 MFD, 15V.
5. ALL DIODES ARE INAC01.
6. J1 - 1 POWER GND.
7. J2 - 1 LOGIC GND.
8. PROVISIONS MADE ON PC LAYOUT FOR IN4001 DIODES MAY BE LEFT OUT IF TRANSISTOR TYPES 2N6041 & 2N6044 ARE USED.
9. THIS SCHEMATIC VALID FOR ASSY REV "A" PCN 0660

10. DESIGNATES COMPONENTS ARE NOT USED.

J	K	REVISIONS AND APPROVALS	DATE	
D	H	DESIGNED BY: S LEONG	1-25-77	
E	F	CHECKED BY: GLENN	6/23/77	SCHEMATIC - SPRINT MICRO 3 AUX. PAPERFEED BOARD.
C	D	APPROVED BY: SEE B/M 90702	FS 4/11/77	
A	B	DATE TESTED: 4/4/77	4/4/77	REV 2 PAGE 2 OF 2
PART USED		PART NO.		Q 90700 B