



EXTENDED SYSTEMS MONITOR

USER'S GUIDE



 VECTOR GRAPHIC INC.

EXTENDED SYSTEMS MONITOR

Version 4.0

USERS MANUAL

Revision A

October 15, 1979

Copyright 1979 Vector Graphic Inc.

Extended Systems Monitor User's Manual

Copyright 1979 by Vector Graphic Inc.
All rights reserved.

Disclaimer

Vector Graphic makes no representations or warranties with respect to the contents of this manual itself, even if the product it describes is covered by a warranty or repair agreement. Further, Vector Graphic reserves the right to revise this publication and to make changes from time to time in the content hereof without obligation of Vector Graphic to notify any person of such revision or changes, except when an agreement to the contrary exists.


Revision Numbers

The date and revision of each page herein appears at the bottom of each page. The revision letter such as A or B changes if the manual has been improved but the product itself has not been significantly modified. The date and revision on the Title Page corresponds to that of the page most recently revised. When the product itself is modified significantly, the product will get a new revision number, as shown on the manual's title page, and the manual will revert to revision A, as if it were treating a brand new product. THIS MANUAL SHOULD ONLY BE USED WITH THE PRODUCT(S) IDENTIFIED ON THE TITLE PAGE.

Extended Systems Monitor User's Manual

TABLE OF CONTENTS

<u>Section</u>		<u>Page</u>
General Description.....		1
Table of Hex values.....		2
Command Format		
A - ASCII Dump.....		3
B - Jump to Bootstrap Loader		
C - Compare Blocks		
D - Dump in Hex		
E - External Communications		
F - Find Two Bytes.....		4
G - Go to and Execute		
H - Jump to HI Ram		
I - Input from a Port		
J - Jump to Loaded DOS		
K - Set Breakpoints.....		5
L - Jump to 0000		
M - Move Memory Block		
N - Non-destructive Memory Test		
O - Output to Port		
P - Program Memory.....		6
Q - Compute Checksum		
R - Register Dump		
S - Search for Single Byte		
T - Test Memory.....		7
U - Jump to 2B00		
W - Wide ASCII Dump		
X - Exchange Memory Blocks		
Y - Keyboard Echo		
Z - Zero or Fill Memory.....		8
Entry Points.....		9
Video Driver.....		10
Cursory X Y Positioning.....		12
Keyboard Code Conversion for Vector Graphic Keyboards.....		12
Using the I/O Routines.....		13
Other Useful Monitor Routines.....		14
Monitor Listing.....		15 - 36



Extended Systems Monitor User's Manual

GENERAL DESCRIPTION

The Version 4.0 Monitor is a complete systems Monitor, able to support the Flashwriter II (80 X 24) board, and the Vector Graphic Keyboard. Thus it is recommended for use with the Mindless Terminal. All keyboard and video I/O can be done through the Monitor's I/O routines, freeing higher level software from carrying a variety of versions for different hardware configurations. Since version 4.0 does not work with serial terminals, use the 2.1 version for this purpose.

Version 4.0 differs from 3.1 in the following key ways:

- 1) Improved video driver, with a number of additional commands that software can use to manipulate the screen, and easier X-Y positioning.
- 2) A breakpoint executive command, for quick debugging.
- 3) A communications program that allows you to use a Vector Graphic system as a dumb terminal. (Executive command "E").
- 4) Space to include up to 15 keyboard conversions for foreign language keyboards.
- 5) Much easier to use Executive commands.
- 6) Control-Q no longer can be used to return to the Monitor Executive.

In addition to I/O, the Monitor includes an extensive command executive, a compactly written program designed to facilitate manipulation and display of memory data. The "prompt" which indicates that the Monitor Executive is waiting for operator entry is an asterisk (*).

There are 24 commands which are entered as a single letter followed by up to four hexadecimal data fields. After each field is entered, a space is automatically output as a prompt. Either upper or lower case alpha characters may be used, but lower case characters will be converted to upper case, and any non-hex characters will be ignored. Allowable hex characters are 0-9, A-F. Address fields are four digits long; other fields are two digits long. The executive is useful in debugging hardware and software, particularly assembly language software, because it is resident in the system.

If a space is typed at any time during field entry, a default value of zero is assumed for all leading zeroes. This applies to an entire field as well as one that has been partially entered, and the cursor will advance to the next field if required. For example, typing (SP) will have the same effect as typing 0000; typing 100(SP) will have the same effect as 0100.

Any command that generates a display can be temporarily halted with a space and continued with another space. The ESCape key will abort a display or command entry.

The 4.0 Monitor is located at address E000 - E7FF in new Vector Graphic systems. If it is purchased for another location, address references in this manual should be understood accordingly.

The hexadecimal number system may seem confusing if you are not familiar with it, but it has become the standard of the microcomputer field and is clearly the best system with 16 bit addresses and 8 bit data. It is usually not necessary to convert between number systems, as this is usually done by software (i.e. assemblers). Remembering a few values in hex should make things easy:

HEX NUMBER	DECIMAL VALUE	JARGON	BINARY BITS
A	10		4
B	11		4
C	12		4
D	13		4
E	14		4
F	15		4
10	16		5
FF	255		8
100	256	1 PAGE	9
3FF	1,023		10
400	1,024	1K	11
FFF	4,095		12
1000	4,096	4K	13
4000	16,384	16K	15
8000	32,768	32K	16
FFFF	65,535	64K-1	16

The familiar rules of arithmetic work just the same in hex as in decimal:

$$\begin{array}{r} & \overset{10}{\text{ }} \\ 40) & \overline{400} \end{array} \quad \text{Hex (trivial)}$$

Extended Systems Monitor User's Manual

COMMAND FORMAT

*A <ADR1> <ADR2> - ASCII DUMP

Memory contents from ADR1 through ADR2 will be displayed as ASCII characters, or graphic symbols for values less than 20 hex. If the most significant bit is high, reverse video is displayed. This command is useful for examining files such as those created by the lineditor, BASIC or the WORD MANAGEMENT SYSTEM. ASCII strings embedded in object code are easy to recognize.

*B - JUMP TO BOOTSTRAP LOADER

Typing this command will cause a jump to location F800H which is the disk bootstrap loader. This will cause the disk operating system disk to be loaded into memory and transfer control to MDOS.

*C <ADR1> <ADR2> <ADR3> - COMPARE BLOCKS

A byte-by-byte comparison will be made between the block of memory data starting at ADR1 and ending at ADR2 and a block of identical length starting at ADR3. The differences will be printed out with the address, the byte in the first block and the byte in the second block. This command is useful to compare two versions of a program or to verify that proms have been programmed correctly.

*D <ADR1> <ADR2> - DUMP IN HEX

Memory contents from ADR1 through ADR2 will be displayed as pairs of hexadecimal characters. The left character in each pair represents the four most significant bits of the memory location. The display may be halted and interrupted as described above. The ASCII representation is displayed in a column on the right.

*E - EXTERNAL COMMUNICATIONS

The monitor will output anything typed on the keyboard through port 4 on the Bitstreamer II I/O board or an appropriately addressed Bitstreamer I board. Anything received on this port will be displayed on the screen. Normally a 300 baud modem would be connected to the serial RS 232 output from the I/O board, and this feature allows the system to be used as a simple terminal to communicate with a host in a full duplex mode. Operation at speeds above 300 baud requires the host to send null characters after linefeeds, so that characters are not lost when the screen scrolls up.

***F <ADR1> <ADR2> <BYTE1> <BYTE2> - FIND TWO BYTES**

This memory range from ADR1 through ADR2 will be searched for the particular code combination BYTE 1 BYTE 2. This is useful for locating particular commands or jump addresses. For example, if you wish to change a control character (say control D) in a program you may try FE 04, which is CPI 04 since this is a common way of testing input characters. If you wish to find all locations that call or jump to a particular address, say C700, then search for 00C7. There is no guarantee that each location displayed is valid object code - it may be part of a data table, ASCII string, or second and third bytes of a three byte instruction.

***G <ADR1> - GO TO AND EXECUTE**

This command will cause a jump to ADR1 to execute a program or user subroutine. As with all Monitor jump commands, the address contained on the stack is "START" (C00B) and if the user routine at ADR1 ends in "RET", program execution will return to the Monitor. Virtually unlimited stack space is available (up to 1K), but of course, pushing more registers on the stack than are popped will defeat the return feature with undesirable effects.

***H - JUMP TO HI RAM**

This command jumps to FC00 which is the start of the 1K scratchpad RAM. This is a useful area for small machine language programs.

***I <PORT> - INPUT FROM A PORT**

Execution of this command will cause the CPU to execute an "IN PORT" instruction and the accumulator contents immediately following this to be displayed. This command is useful in checking out peripheral equipment. Only those ports used by the terminal, cassette interface, etc., will contain interesting values. All others will read FF since the data bus will be floating when the "IN" command is executed.

***J - JUMP TO LOADED DOS**

This command permits easy return to the MDOS disk operating system at 0437H, or if not present, jump will be 0437H, which is the MDOS entry location and is subject to change in future releases.

Extended Systems Monitor User's Manual

***K - SET BREAKPOINTS**

This command expects a 4 digit address, and will place a RESTART 7 (FF) at that location in RAM. When that instruction is executed, which is a call to location 8, the CPU will jump to the monitor routine that dumps the register contents. The instruction replaced with FF will also be restored. Entry of the monitor at E000 will clear the breakpoint, as will pressing the RESET switch.

***M <ADR1> <ADR2> <ADR3> - MOVE MEMORY BLOCK**

The data contained in memory starting at ADR1 and ending at ADR2 is moved to memory locations starting at ADR3. This command is useful for moving a program from a temporary storage location to its correct address. If there is an overlap of the two memory areas, interesting results are obtained. For example, M 6000 7BFF 6400 will cause the block of data from 6000 through 63FF to be repeated 8 times from 6000 through 7FFF, since by the time location 6400 is read, it has been overwritten with data from 6000. This is useful for bank programming of proms, or for creating repeating instruction sequences for test purposes.

***N - NON-DESTRUCTIVE MEMORY TEST**

Memory locations starting at 0000 are read and the data temporarily stored. The memory location is then tested to see if 00 and FF can be written and read correctly. This continues after rewriting the original data until the first error is detected, whereupon the address is displayed followed by the data written into memory and what was read from it. This command is most useful for checking how much memory a system contains. For example, if the system contains 16K of memory, 4000 00 FF should be printed, indicating that there is no memory at address 4000. Since the test is non-destructive to data in memory, it can be used at any time.

***O <PORT> <DATA> - OUTPUT TO PORT**

The two hex digits "DATA" are loaded into the accumulator and the instruction "OUT PORT" is executed. This command is useful for checking our peripheral equipment. For example, if a printer is connected to I/O port 6, 0 06 41 will cause an "A" to be printed since 41 is the hex ASCII code for "A".

***P <ADR1> - PROGRAM MEMORY**

The contents of 16 bytes of memory containing ADR1 are displayed in both hex and ASCII, allowing preceding and following instructions to be viewed. Advancing to the next instruction is accomplished by typing space or cursor right (\rightarrow). Backspace or cursor left (\leftarrow) goes backwards. The cursor up and down keys move to an adjacent 16 byte block. Any hex characters typed will replace the existing contents of RAM. After every keypress, the screen display is refreshed by reading from memory, so the display reflects the exact memory contents. To terminate, depress ESCAPE.

***Q <ADR1> <ADR2> - COMPUTE CHECKSUM**

The MOD 256 checksum of memory contents in the address range specified is computed and displayed. This command is useful for checking proms or files to see if anything has changed. Any source file or program written in pure code (it does not write on itself) will have the same checksum as when it was loaded. While debugging assembly language programs, it is useful to be able to verify that a program being debugged has not written garbage in the source file or assembler.

***R - REGISTER DUMP**

This command will print a header identifying the Z-80 registers, and immediately below it the contents of all the registers. The flags are displayed with the letters Z C M E H for the zero, carry, minus, parity even, and auxiliary or half carry flags respectively. The presence of the letter indicates the flag is true. The contents of the memory locations pointed to by the B, D, and H register pairs are also displayed as is the return address on the stack.

***S <ADR1> <ADR2> <BYTE> - SEARCH FOR SINGLE BYTE**

This is similar to the "F" command, except that only one byte is searched for instead of two. An example of the use of this command is to display all locations in a program where an output to a port occurs (D3). The address of each location will be displayed followed by "D3" and the next byte (the port number).

Extended Systems Monitor User's Manual

***T <ADR1> <ADR2> - TEST MEMORY**

This is an extremely useful command, especially when first setting up a system. This command permits thorough testing of the system memory. A portion of a 64K byte pseudorandom number sequence is written into memory from ADR1 through ADR2, and the exact same sequence is regenerated from the initial point and compared with what is read from memory. If all locations compare, another portion of the sequence is used to repeat the test which continues until it is interrupted. Any memory errors are displayed with the address, what was written into memory and what was read from memory, respectively. This information is all that is needed to pinpoint a malfunctioning memory chip. This test is quite exhaustive if used for at least 10 cycles and is far superior to incrementing or complementing tests which may not reveal addressing problems. The only area of system memory that cannot be tested with this routine is the few bytes required for the stack and video flags in the vicinity of FFD0 on the 2708 PROM/RAM board.

***U - JUMP TO 2B00**

This command permits easy return to programs in the user application area of MDOS.

***W <ADR1> <ADR2> - WIDE ASCII DUMP**

This is similar to the "A" command, but with a full screen width display.

***X <ADR1> <ADR2> <ADR3> - EXCHANGE MEMORY BLOCKS**

A block of memory from ADR1 through ADR2 is exchanged with an equal length block starting at ADR3. This command is useful in comparing the operation of two versions of a program, or for rapid switching of portions of a program without destroying the original. A loaded BASIC program can be exchanged with another if care is used to include the stack area (usually below the top of allowed memory).

***Y - KEYBOARD ECHO**

This command causes keyboard input to be echoed directly to the video driver and can be used for demonstration purposes. An ESCape returns to the Monitor.

***Z <ADR1> <ADR2> <DATA> - ZERO OR FILL MEMORY**

The memory block from ADR1 through ADR2 is filled with the byte "DATA". This is useful for setting memory to Zero. The end of a file or assembled program will stand out more clearly if memory is first zeroed. For test purposes, single instructions can be executed continuously so that bus waveforms are more easily interpreted. This is done by filling a block of memory with a repeated instruction sequence with a jump to the start of the block so that the program loops continuously.

ENTRY POINTS

A jump table at the beginning of the Monitor can be used to access several routines:

E000 - The normal cold entry point to the Monitor Executive, this is a jump to the initialization routine which clears the screen and initializes 8251 USARTS through I/O ports 3, 5, and 7. This is compatible with the Bitstreamter I addressed starting at port 4 or the Bistreamer II addressed starting at port 2. The USARTS are set for an X16 baud rate factor and other parameters as would be used with a serial printer or extra terminal.

E003 - This is a jump to the routine which should be used for console keyboard status test. Return with the zero flag set indicates no keyboard input.

E006 - This is a jump to the keyboard data input which returns with the character in the "A" register. The keyboard code conversions described below are carried out. There is no checking for ESC key depression.

E009 - This is a jump to the video driver which displays the character in "A" on the screen.

E00C - This is a jump to the "ESCAPE" routine which returns zero if no input, or with the character in the "A" register if there is. Keyboard code conversions are carried out. If the ESC key was pressed, the system returns to the Monitor Executive.

VIDEO DRIVER

Version 4 of the Monitor contains a more elaborate video driver than previous versions. The purpose of the video driver is to accept a stream of ASCII codes, and to write them into the screen memory in the proper place, interpreting certain non printing control codes in a special way. There are several entry points to the video driver. E009 is recommended. The character code to be printed must be in the A register. A CALL E009 will cause the character to be printed on the screen at the cursor position. All registers will be preserved.

Control codes are generated by the keyboard by holding the control (CTRL) key down while a letter key is pressed. Control codes have values between 0 and 31, and are 64 less than the codes for the corresponding upper case letters. To demonstrate the features of the video driver, type Y after the Monitor prompt, and any keyboard generated code will be echoed to the video driver. The following control codes are interpreted as special functions, while all others are ignored:

- (B) HOME THE CURSOR
- (D) CLEAR THE SCREEN AND HOME CURSOR
- (E) DISPLAY THE CODE IN B REGISTER
- (H) DESTRUCTIVE BACKSPACE (also BACKSPACE key)
- (I) TAB OVER TO THE NEXT 8 MULTIPLE (also TAB)
- (J) LINEFEED (also LF Key)
- (M) CARRIAGE RETURN (also RETURN key)
- (N) TOGGLE CURSOR
- (P) CLEAR TO END OF SCREEN
- (Q) CLEAR TO END OF LINE
- (R) CURSOR DOWN (also ↓)
- (T) TOGGLE REVERSE VIDEO
- (U) CURSOR UP (also ↑)
- (W) CURSOR LEFT (also ←)
- (X) CLEAR TO START OF LINE
- (Z) CURSOR RIGHT (also →)
- ESC CURSOR XY POSITION LEAD-IN

Experiment with the keys. There are special keys on the keyboard to generate some of the codes such as RETURN, TAB and linefeed (LF). If you are using the Vector Graphic Keyboard or Mindless Terminal, there are also keys for the cursor control and BACKSPACE. A few of the functions are not self explanatory. A Control D sets the reverse video flag to normal in addition to clearing the screen and homing the cursor. A Control T will then toggle the reverse video flag from normal to reverse and back without printing on the screen.

Extended Systems Monitor User's Manual

In some cases it is desireable to print the symbol for a control code on the screen. This can be done in assembly language programs by putting the code for the symbol in the B register and calling the video driver with Control E (05) in A. Enter the folowing machine code at FC00 and execute it to demonstrate this feature:

```
at FC00  06 02 3E 05 04 CD 09 E0 CD OC E0 C3 02 FC
```

CURSOR X Y POSITIONING

Many programs utilize random X Y positioning of the cursor. This is done by outputting a three byte sequence to the video driver. The first code is ESC (1BH) followed by the desired X position and Y position in hex. The top left corner of the screen is 0, 0. The sequence 1B 08 40 would cause the cursor to move to line 8, character position 64 on the screen. This feature can not be demonstrated using the keyboard since ESC causes a return to the monitor.

The video driver provides an extensive range of special controls, however, they must be incorporated into the software generating the video stream to be meaningful. For instance a piece of software that merely echoes all characters as they go into its input buffer will allow cursor motion on the screen, but this will probably be meaningless to the software.

KEYBOARD CODE CONVERSION - VECTOR GRAPHIC KEYBOARDS

Due to limitations in the keyboard encoder chip, the [] key on Vector Graphic keyboards is not encoded properly. The correct code is generated by a conversion routine in the Monitor's CONVERT routine. The codes for backslash and tilde are also produced by the control and control shift mode of this key.

[] KEY CONVERSION:

MODE	KEYCODE	CONVERTED CODE	ASCII SYMBOL
unshifted	F1	5B	[
shifted	E1	5D]
control	B1	5C	\
control shift	A1	7E	~

The cursor up key is also converted from 60H to 15H which is interpreted correctly by the video driver. Room is provided in the routine for up to 15 keycode conversions. Foreign languages require additional conversions, and versions are available for French, German, Swedish and Spanish. It is essential that software utilize the monitor conversion routine for this reason.

USING THE I/O ROUTINES

The I/O routines in the Monitor are used as the Main System I/O in Vector Graphic Systems. This makes software I/O independent and easily interchangeable between systems. An example of how this is done is shown below:

INPUT ROUTINE:	INPT	CALL E00CH JZ INPT RET (RETURNS WITH CHAR INPUT IN A)
OUTPUT ROUTINE:	OUTPT	JMP E009H (CHARACTER IN A)
BREAK TEST:	CCNTL	CALL E00CH RET (RETURNS WITH ZERO FLAG SET IF NO INPUT, OR CHARACTER IN A. JUMPS TO MONITOR EXECUTIVE IF ESCAPE INPUT.)

Note that either the ESC key will break to the Monitor, which provides a convenient way of transferring control from any executive such as the DOS or BASIC to the Monitor, but necessitates the use of another character (Control C is standard) for a single level break. The routines above are merely given to illustrate how simple it is to use the Monitor I/O routines. Many programs require additional instructions to move the character to be output into the accumulator, or may require different flag conditions or accumulator contents on return from the input and Break Test routine, but the variations are easily implemented.

OTHER USEFUL MONITOR ROUTINES

The Monitor contains a number of routines that can be called by user programs, and which will save considerable programming effort. In addition to the keyboard input and video output described elsewhere, we have:

AHEX inputs four hex digits from the keyboard and returns the binary value in D,E registers. A space is automatically output at the end. All registers, except B, are used. Entry at AHEO with a value of 1-3 in C will convert that many digits. Non hex values will be ignored.

CRLF will output a carriage return and line feed to the screen. The A register is used.

SPCE will output a space to the screen. The A register is used.

RNDM returns a new random number in B,C based on the seed in B,C as it is called. B,C should not contain 0000. The pseudorandom number sequence generated is $2^{16}-1$ entries long and is based on a software simulation of a shift register with maximum length feedback. PSW is used.

PTAD first outputs a CRLF, then outputs the binary value in H,L as four hex digits followed by a space. PSW used.

PT2 outputs (A) as two hex digits.

TAHEX calls AHEX twice, inputting two address fields of four hex digits. The first value is returned in H,L; the second in D,E.

Extended Systems Monitor User's Manual

Page 1

Addr	B1	B2	B3	B4	E	Line	Label	Opnd	Operand
0000		E000	=	0000	BASE			EQU	0E000H ;ASSEMBLY ADDRESS
0000		E000	=	0010	PR			EQU	0E000H ;PROM/RAM ADDRESS
0000				0020			LINK	'M6'	
0000						0000	*****	VECTOR MZ MONITOR - VERSION 4.0	*****
0000						0010	*	R. S. HARP 7/16/79	*
0000						0020	*	SYSTEM 3 VERSION	*
0000						0030	*	ASSEMBLES AT C OR E	*
0000						0040	*	ONLY FOR FLASHWRITER II	*
0000						0050	*****	*****	*****
0000						0060	*		
0000						0070	*	SYSTEM EQUATES	
0000		0000	=	0080	CONS		EQU	0	;CONS STATUS PRT
0000		0001	=	0090	COND		EQU	1	;CONS DATA PORT
0000		0040	=	0100	RDA		EQU	40H	;RECEIVE FLAG
0000		0000	=	0110	STPOL		EQU	0	;STATUS POLARITY
0000		FFD0	=	0120	SPTR		EQU	PR+01FD0H	;STACK POINTER
0000				0130	*				
0000				0140	*****	COMMAND FORMAT	*****		
0000				0150	*	A SSSS FFFF ASCII DUMP OF MEMORY			*
0000				0160	*	B JUMP TO BOOTSTRAP LOADER			*
0000				0170	*	C SSSS FFFF CCCC COMPARE BLOCKS			*
0000				0180	*	D SSSS FFFF DUMP MEMORY IN HEX & ASCII			*
0000				0190	*	E EXTERNAL COMMUNICATIONS			*
0000				0200	*	F SSSS FFFF DD DD TWO BYTE SEARCH			*
0000				0210	*	G SSSS GO TO AND EXECUTE			*
0000				0220	*	H JUMP TO HIGH RAM AT FC00			*
0000				0230	*	I PP INPUT FROM PORT			*
0000				0240	*	J JUMP TO DOS			*
0000				0250	*	K LLLL SET A BREAKPOINT			*
0000				0255	*	L JUMP TO LOW RAM AT 0			*
0000				0260	*	M SSSS FFFF DDDD MOVE BLOCK			*
0000				0270	*	N NON DESTRUCTIVE MEMORY TEST			*
0000				0280	*	O PP DD OUTPUT TO PORT			*
0000				0290	*	P LLLL PROGRAM MEMORY			*
0000				0300	*	Q SSSS FFFF COMPUTE CHECKSUM			*
0000				0310	*	R DUMP Z-80 REGISTERS			*
0000				0320	*	S SSSS FFFF DD SEARCH FOR SINGLE BYTE			*
0000				0330	*	T SSSS FFFF TEST MEMORY			*
0000				0340	*	U JUMP TO USER AREA AT 2800			*
0000				0350	*	X SSSS FFFF DDDD EXCHANGE BLOCK			*
0000				0360	*	Y KEYBOARD ECHO			*
0000				0370	*	Z SSSS FFFF DD ZERO OR FILL MEMORY			*
0000				0380	*****	*****	*****		
0000				0390	*				
0000				0400		ORG	BASE		
0000				0410	*	JUMP TABLE OF ENTRY POINTS			
E000	C3	16	E0	0420	MONIT	JMP	INIT		;INITIALIZE ALL
E003	C3	3C	E1	0430	KEYTST	JMP	KEYSTAT		;TEST KEYBOARD
E006	C3	41	E1	0440	KEYDATA	JMP	CONVERT		;INPUT KEYBOARD
E009	C3	3A	E3	0450	CRT	JMP	VIDEO		;OUTPUT TO SCREEN
E00C	C3	2F	E1	0455	ESC	JMP	ESCAPE		;KEYBOARD INPUT
E00F				0460	*				
E00F	D3	03		0470	OTPRTS	OUT	3		
E011	D3	05		0480		OUT	5		
E013	D3	07		0490		OUT	7		
E015	C9			0500		RET			

Extended Systems Monitor User's Manual

Page 2

Addr	B1	B2	B3	B4	E	Line Label	Opcd	Operand	
E016	31	D0	FF			0510 INIT	LXI	SP,SPTR	;INIT STACK
E019	CD	2F	E1			0520	CALL	ESCAPE	;DUMP LATCH
E01C	AF					0530	XRA	A	
E01D	32	EA	FF			0535	STA	XYFLAG	
E020	CD	0F	E0			0540	CALL	OTPRTS	
E023	CD	0F	E0			0550	CALL	OTPRTS	
E026	CD	0F	E0			0560	CALL	OTPRTS	
E029	3E	40				0570	MVI	A,40H	;RESET USART
E02B	CD	0F	E0			0580	CALL	OTPRTS	
E02E	3E	C2				0590	MVI	A,OCEH	;MODE
E030	CD	0F	E0			0600	CALL	OTPRTS	
E033	3E	27				0610	MVI	A,27H	;COMMAND
E035	CD	0F	E0			0620	CALL	OTPRTS	
E038						0630 * PATCH RST 7			
E038	3E	C3				0640	MVI	A,OC3H	;JUMP
E03A	32	38	00			0650	STA	38H	;RST 7
E03D	21	DB	E6			0660	LXI	H,DUMPREGS	
E040	22	39	00			0670	SHLD	39H	
E043						0680 * DISPLAY SIGN ON			
E043	CD	DC	E4			0690	CALL	SIGN	
E046						0700 * CLEAR BREAKPOINT			
E046	2A	E7	FF			0710 CLRBRK	LHLD	BKPTLOC	
E049	11	E9	FF			0720	LXI	D,BRKCODE	
E04C	ED	53	E7	FF		0730	SDED	BKPTLOC	
E050	1A					0740	LDAX	D	
E051	77					0750	MOV	M,A	
E052	31	D0	FF			0755 START	LXI	SP,SPTR	;INITIALIZE STACK
E055	CD	38	E5			0760	CALL	PROMPT	
E058	CD	2F	E1			0770	CALL	ESCAPE	;READ KEYBOARD
E053	23	F0				0780	JRZ	START+6	
E05D	26	5F				0790	ANI	5FH	;UPPER AND LOWER
E05F	21	52	E0			0800	LXI	H,START	
E062	E5					0810	PUSH	H	
E063	FE	04				0820	CPI	'D'-64	
E065	CC	8A	E3			0830	CZ	VIDEO	;ECHO CLEARSCN
E063	FE	41				0840	CPI	'A'	
E06A	D3					0850	RC		;TOO SMALL
E06B	FE	5B				0860	CPI	0SBH	
E06D	DO					0870	RNC		;TOO LARGE
E06E	21	F9	E0			0880	LXI	H,CMDTB+7EH	
E071	F5					0890	PUSH	PSW	
E072	87					0900	ADD	A	
E073	35					0910	ADD	L	
E074	65					0920	MOV	L,A	
E075	5E					0930	MOV	E,M	
E076	23					0940	INX	H	
E077	56					0950	MOV	D,M	
E073	EB					0960	KCHG		
E079	F1					0970	POP	PSW	
E07A	E9					0980	PCNL		;AWAY WE GO
E07B						0990 * COMMAND TABLE			
E07B	47	E5				1000 CMDTB	DW	WASCII	;A
E07D	47	E2				1010	DW	BOOT	;B
E07F	F1	E2				1020	DW	COMPR	;C
E081	CB	E5				1030	DW	HEXRUL	;D
E083	E0	E7				1040	DW	EXTCOM	;E

Extended Systems Monitor User's Manual

Page 3

Addr	B1	B2	B3	B4	E	Line	Label	Opcd	Operand
E085	14	E3				1050		DW	FIND ;F
E087	AF	E0				1060		DW	EXEC ;G
E089	65	E2				1070		DW	RAM ;H
E08B	62	E3				1080		DW	PINPT ;I
E08D	96	E1				1090		DW	WARM ;J
E08F	C5	E7				1100		DW	SETBRK ;K
E091	71	E2				1110		DW	LORAM ;L
E093	A5	E2				1120		DW	MOVEB ;M
E095	CD	E2				1130		DW	NDMT ;N
E097	74	E3				1140		DW	POUTP ;O
E099	18	E6				1150		DW	PROGRAM ;P
E09B	79	E1				1160		DW	CHKSM ;Q
E09D	CF	E6				1170		DW	DREGS ;R
E09F	21	E3				1180		DW	SRCH ;S
EOA1	C3	E1				1190		DW	TMEM ;T
EOA3	56	E2				1200		DW	USER ;U
EOA5	52	E0				1210		DW	START ;V
EOA7	52	E0				1220		DW	START ;W
EOA9	96	E2				1230		DW	EXCHG ;X
EOAB	AE	E1				1240		DW	ECHO ;Y
EOAD	7D	E2				1250		DW	ZEROM ;Z
EOAF						1260	*		
EOAF						1270	*** EXECUTE THE PROGRAM AT THE ADDRESS ***		
EOAF						1280	*		
EOAF	CD	D1	E4			1290	EXEC	CALL	PTSTNG
E0B2	47	4F	20	54		1300		DTH	'GO TO '
E0B6	4F	A0							
E0B8	CD	BD	E0			1310		CALL	AHEX ;READ ADD FROM KB
E0BB	EB					1320		XCHG	
E0BC	E9					1330		PCHL	;JUMP TO IT
E0BD						1340	*		
E0BD						1350	*** CONVERT UP TO 4 HEX DIGITS TO BIN		
E0BD						1360	*		
E0BD	0E	04				1370	AHEX	MVI	C,4 ;COUNT OF 4 DIGIT
E0BF	21	00	00			1380	AHE0	LXI	H,0 ;16 BIT ZERO
E0C2	CD	2F	E1			1390	AHE1	CALL	ESCAPE
E0C5	FE	20				1400		CPI	' '
E0C7	CA	E8	E0			1410		JZ	SPCOVR
E0CA	CD	ED	E0			1420		CALL	HEX ;CHECK VALUE
E0CD	38	F3				1430		JRC	AHE1
E0CF	29					1440		DAD	H ;MULT H*16
E0D0	29					1450		DAD	H
E0D1	29					1460		DAD	H
E0D2	29					1470		DAD	H
E0D3	35					1480		ADD	L
E0D4	6F					1490		MOV	L,A
E0D5	0D					1500		DCR	C
E0D6	C2	C2	E0			1510		JNZ	AHE1 ;4 DIGITS?
E0D9	EB					1520		XCHG	KEEP READING
E0DA	3E	20				1530	SPCE	MVI	A,20H ;PRINT SPACE
E0DC	C3	8A	E3			1540	PTCN	JMP	VIDEO
E0DF	3E	0D				1550	CRLF	MVI	A,ODH ;PRINT CR
E0E1	CD	DC	E0			1560		CALL	PTCN
E0E4	3E	0A				1570		MVI	A,0AH
E0E6	18	F4				1580		JR	PTCN
E0E8						1590	*		

Extended Systems Monitor User's Manual

Page 4

Addr	B1	B2	B3	B4	E	Line	Label	Opcd	Operand
E0E8	CD	8A	E3			1600	SPCOVR	CALL	VIDEO
E0EB	18	EC				1610		JR	SPCE-1
E0ED						1620	*		
E0ED						1630	* CHECK FOR HEX VALUE, CONVERT		
E0ED	FE	30				1640	HEX	CPI	30H ;<0
E0EF	D8					1650		RC	
E0F0	FE	3A				1660		CPI	'.'
E0F2	38	09				1670		JRC	NUM
E0F4	36	5F				1675		ANI	5FH ;UPPER & LOWER CAS
E0F6	FE	41				1680		CPI	'A'
E0F8	D8					1690		RC	
E0F9	FE	47				1700		CPI	'G'
E0FB	3F					1710		CMC	
E0FC	D8					1720		RC	
E0FD	CD	8A	E3			1730	NUM	CALL	VIDEO
E100	D6	30				1740		SUI	48 ;ASCII BIAS
E102	FE	0A				1750		CPI	10 ;DIGIT 0-10
E104	38	02				1760		JRC	ALFA
E106	D6	07				1770		SUI	7 ;ALPHA BIAS
E108	A7					1780	ALFA	ANA	A ;CLEAR CY
E109	C9					1790		RET	;WITH CY CLEAR
E10A						1800	*		
E10A						1810	* READ 2 DIGITS FROM THE CONSOLE		
E10A	OE	02				1820	AHE2	MVI	C,2
E10C	18	B1				1830		JR	AHEO
E10E						1840	*		
E10E						1850	* SHORT ROUTINE TO SAVE CODE.		
E10E	CD	BD	E0			1860	TAHEX	CALL	AHEX
E111	18	AA				1870		JR	AHEX
E113						1880	*		
E113						1890	*** READ FROM CONSOLE TO REG A ***		
E113						1900	*		
E113	CD	2F	E1			1910	RDCN	CALL	ESCAPE ;READ KEYBOARD
E116	28	FB				1920		JRZ	RDCN
E118	FE	60				1930		CPI	60H
E11A	38	CO				1940		JRC	PTCN
E11C	E6	5F				1950		ANI	5FH
E11E	18	BC				1960		JR	PTCN
E120						1970	*		
E120	CD	2F	E1			1980	PAUSE	CALL	ESCAPE
E123	FE	20				1990		CPI	20H
E125	CO					2000		RNZ	
E126	CD	2F	E1			2010	PLOOP	CALL	ESCAPE
E129	FE	20				2020		CPI	20H
E12B	C2	26	E1			2030		JNZ	PLOOP
E12E	C9					2040		RET	
E12F						2050	*		
E12F	CD	30	E1			2060	ESCAPE	CALL	KEYSTAT
E132	C8					2070		RZ	
E133	CD	41	E1			2080		CALL	CONVERT
E136	FE	1B				2090		CPI	1BH ;ESCAPE
E138	CA	52	E0			2100		JZ	START
E13B	C9					2110		RET	
E13C						2120	*		
E13C	DB	00				2130	KEYSTAT	IN	CONS
E13E	E6	40				2140		ANI	RDA

Extended Systems Monitor User's Manual

Page 5

Addr	B1	B2	B3	B4	E	Line	Label	Opcd	Operand
E140	C9					2150		RET	
E141						2160	*		
E141						2170	* KEYBOARD CODE CONVERSION		
E141	DB	01				2180	CONVERT	IN COND	;KEYBOARD DATA
E143	E5					2190		PUSH H	
E144	C5					2200		PUSH B	
E145	01	05	00			2210		LXI B, TABLEND-KTABL/2	
E148	21	5B	E1			2220		LXI H, KTABL	
E148	ED	A1				2230	LOOP	CCI	;COMPARE TABLE
E14D	28	06				2240		JRZ FND	
E14F	23					2250		INX H	
E150	EA	4B	E1			2260		JPE LOOP	;CONT LOOKING
E153	18	01				2270		JR NFND	
E155	7E					2280	FND	MOV A,M	;NEW CODE
E156	E6	7F				2290	NFND	ANI 7FH	;MASK DOWN
E158	C1					2300		POP B	
E159	E1					2310		POP H	
E15A	C9					2320		RET	
E15B						2330	*		
E15B						2340	* THIS TABLE CAN BE EXTENDED IF DESIRED		
E15B	E1	5D				2350	KTABL	DD 0E15DH	;]
E15D	F1	5B				2360		DD 0F15BH	;L
E15F	A1	7E				2370		DD 0A17EH	;
E161	B1	5C				2380		DD 0B15CH	;\
E163	60	15				2390		DD 06015H	;CURSOR UP
E165	E165	=				2400	TABLEND	EQU \$	
E165						2410		ORG KTABL+30	;ROOM FOR 15 CONV
E179						2420	*		
E179						2430	* CHECKSUM ROUTINE		
E179	CD	D1	E4			2440	CHKSM	CALL PTSTNG	
E17C	43	48	45	43		2450		DTH 'CHECKSUM'	
E180	4B	53	55	4D					
E184	A0								
E185	CD	0E	E1			2460		CALL TAHEX	
E188	06	00				2470		MVI B,0	
E18A	7E					2480	CHKSMLP	MOV A,M	
E18B	30					2490		ADD B	
E18C	47					2500		MOV B,A	
E18D	CD	3F	E2			2510		CALL BMP	
E190	20	F8				2520		JRNZ CHKSMLP	
E192	73					2530		MOV A,B	
E193	C3	26	E2			2540		JMP PT2	
E196						2550	*		
E196						2560	* WARM START		
E196						2570	*		
E196	CD	D1	E4			2580	WARM	CALL PTSTNG	
E199	4A	55	4D	50		2590		DTH 'JUMP TO DOS'	
E19D	20	54	4F	20					
E1A1	44	4F	D3						
E1A4	21	E7	04			2600		LXI H,04E7H	;MDOS RESTART
E1A7	7E					2610		MOV A,M	
E1A8	FE	C3				2620		CPI 0C3H	
E1AA	C2	00	00			2630		JNZ 0	;CP/M RESTART
E1AD	E9					2640		PCHL	;MDOS WARM START
E1AE						2650	*		
E1AE						2660	* KEYBOARD ECHO ROUTINE		

Extended Systems Monitor User's Manual

Page 6

Addr	B1	B2	B3	B4	E	Line Label	Opcd	Operand
E1AE	CD	D1	E4			2670 ECHO	CALL	PTSTNG
E1B1	45	43	48	4F		2680	DTH	'ECHO KEYS '
E1B5	20	4B	45	59				
E1B9	53	A0						
E1BB	CD	2F	E1			2690 ECOLP	CALL	ESCAPE
E1BE	C4	DC	E0			2700	CNZ	PTCN
E1C1	13	F8				2710	JR	ECOLP
E1C3						2720 *		;LOOK AT KEYBOARD
E1C3						2730 *** MEMORY TEST ROUTINE ***		;PRINT IF KEYPRES.
E1C3						2740 *		;CONTINUE LOOPING
E1C3	CD	D1	E4			2750 TMEM	CALL	PTSTNG
E1C6	54	45	53	54		2760	DTH	'TEST '
E1CA	A0							
E1CB	CD	OE	E1			2770	CALL	TAHEX
E1CE	01	5A	5A			2780	LXI	B,5A5AH
E1D1	CD	FD	E1			2790 CYCL	CALL	RNDM
E1D4	C5					2800	PUSH	B
E1D5	E5					2810	PUSH	H
E1D6	D5					2820	PUSH	D
E1D7	CD	FD	E1			2830 TLOP	CALL	RNDM
E1DA	70					2840	MOV	M,B
E1DB	CD	3F	E2			2850	CALL	BMP
E1DE	C2	D7	E1			2860	JNZ	TLOP
E1E1	D1					2870	POP	D
E1E2	E1					2880	POP	H
E1E3	C1					2890	POP	B
E1E4	E5					2900	PUSH	H
E1E5	D5					2910	PUSH	D
E1E6	CD	FD	E1			2920 RLOP	CALL	RNDM
E1E9	7E					2930	MOV	A,M
E1EA	B8					2940	CMP	B
E1EB	C4	1D	E2			2950	CNZ	ERR
E1EE	CD	3F	E2			2960	CALL	BMP
E1F1	C2	E6	E1			2970	JNZ	RLOP
E1F4	D1					2980	POP	D
E1F5	E1					2990	POP	H
E1F6	3E	2E				3000	HVI	A,'.'
E1F8	CD	8A	E3			3010	CALL	VIDEO
E1FB	18	D4				3020	JR	CYCL
E1FD						3030 *** THIS ROUTINE GENERATES RANDOM NOS ***		
E1FD	CD	20	E1			3040 RNDM	CALL	PAUSE
E200	73					3050	MOV	A,B
E201	E6	B4				3060	ANI	084H
E203	A7					3070	ANA	A
E204	EA	08	E2			3080	JPE	PEVE
E207	37					3090	STC	
E208	79					3100 PEVE	MOV	A,C
E209	17					3110	RAL	
E20A	4F					3120	MOV	C,A
E20B	78					3130	MOV	A,B
E20C	17					3140	RAL	
E20D	47					3150	MOV	B,A
E20E	C9					3160	RET	
E20F						3170 *		
E20F						3180 *** ERROR PRINT OUT ROUTINE		
E20F						3190 *		

Extended Systems Monitor User's Manual

Page 7

Addr	B1	B2	B3	B4	E	Line Label	Opcd	Operand	
E20F	CD	DF	E0			3200 PTAD	CALL	CRLF	;PRINT CR,LF
E212	CD	20	E1			3210	CALL	PAUSE	
E215	7C					3220	MOV	A,H	;PRINT
E216	CD	26	E2			3230	CALL	PT2	;ASCII
E219	7D					3240	MOV	A,L	;CODES
E21A	C3	2F	E7			3250	JMP	PT2S	;FOR ADDRESS
E21D				*		3260 *			
E21D	F5					3270 ERR	PUSH	PSW	;SAVE ACC
E21E	CD	0F	E2			3280	CALL	PTAD	;PRINT ADD.
E221	78					3290	MOV	A,B	;DATA
E222	CD	2F	E7			3300	CALL	PT2S	;WRITTEN
E225	F1					3310	POP	PSW	;DATA READ
E226	F5					3320 PT2	PUSH	PSW	
E227	CD	2D	E2			3330	CALL	BINH	
E22A	F1					3340	POP	PSW	
E22B	18	04				3350	JR	BINL	
E22D	1F					3360 BINH	RAR		;SHIFT RHT 4 BITS
E22E	1F					3370	RAR		
E22F	1F					3380	RAR		
E230	1F					3390	RAR		
E231	E6	0F				3400 BINL	ANI	OFH	;LOW 4 BITS
E233	C6	30				3410	ADI	48	;ASCII BIAS
E235	FE	3A				3420	CPI	58	;DIGIT 0-9
E237	DA	DC	E0			3430	JC	PTCN	
E23A	C6	07				3440	ADI	7	;DIGIT A-F
E23C	C3	DC	E0			3450	JMP	PTCN	
E23F				*		3460 *			
E23F	7B					3470 * COMPARE ADDRESSES AND INCREMENT H			
E240	95					3480 BMP	MOV	A,E	
E241	20	02				3490	SUB	L	
E243	7A					3500	JRNZ	GOON	
E244	9C					3510	MOV	A,D	
E245	23					3520	SBB	H	
E246	C9					3530 GOON	INX	H	
E247						3540	RET		
E247				*		3550 *			
E247	CD	D1	E4			3560 * DISK BOOTSTRAP			
E24A	42	4F	4F	54		3570 BOOT	CALL	PTSTNG	
E24E	20	44	49	53		3580	DTH	'BOOT DISK'	
E252	CB								
E253	C3	00	F8			3590	JMP	PR+1800H	
E255				*		3600 *			
E256						3610 * JUMP TO USER RAM			
E256	CD	D1	E4			3620 USER	CALL	PTSTNG	
E259	55	53	45	52		3630	DTH	'USER AREA'	
E25D	20	41	52	45					
E261	C1								
E262	C3	00	2B			3640	JMP	2B00H	
E265				*		3650 *			
E265						3660 * JUMP TO RAM AT PR+1C00			
E265	CD	D1	E4			3670 RAM	CALL	PTSTNG	
E268	43	49	20	52		3680	DTH	'HI RAM'	
E26C	41	CD							
E26E	C3	00	FC			3690	JMP	PR+1COOH	
E271				*		3691 *			

Extended Systems Monitor User's Manual

Page 8

Addr	B1	B2	B3	B4	E	Line Label	Opcd	Operand
E271						3692 * JUMP TO RAM AT 0		
E271	CD	D1	E4			3693 LORAM	CALL	PTSTNG
E274	4C	4F	20	52		3694	DTH	'LO RAM'
E276	41	CD						
E27A	C3	00	00			3695	JMP	0
E27D						3700 *		
E27D						3710 * ZERO OR FILL MEMORY WITH A CONSTANT		
E27D	CD	D1	E4			3720 ZEROM	CALL	PTSTNG
E280	46	49	4C	4C		3730	DTH	'FILL '
E284	A0							
E285	CD	0E	E1			3740	CALL	TAHEX
E288	E5					3750	PUSH	H ;READ ADDRESSES
E289	CD	0A	E1			3760	CALL	AHE2 ;SAVE H
E28C	EB					3770	XCHG	
E28D	E3					3780	XTHL	
E28E	C1					3790	POP	B ;READ 2 DIGITS
E28F	71					3800 ZLOOP	MOV	M,C ;RESTORE H,L
E290	CD	3F	E2			3810	CALL	BMP ;WRITE INTO MEM
E293	C8					3820	RZ	;COMP ADD, INCR H
E294	18	F9				3830	JR	ZLOOP ;RETURN IF DONE
E296						3840 * EXCHANGE OR MOVE A BLOCK OF MEMORY		;CONTINUE TIL DONE
E296	47					3850 EXCHG	MOV	B,A
E297	CD	D1	E4			3860	CALL	PTSTNG
E29A	45	58	43	48		3870	DTH	'EXCHANGE '
E29E	41	4E	47	45				
E2A2	A0							
E2A3	18	09				3880	JR	MOVENTR
E2A5	47					3890	MOV	B,A ;SAVE CODE
E2A6	CD	D1	E4			3900	CALL	PTSTNG
E2A9	4D	4F	56	45		3910	DTH	'MOVE '
E2AD	A0							
E2AE	CD	0E	E1			3920 MOVENTR	CALL	TAHEX ;READ ADDRESSES
E2B1	E5					3930	PUSH	H
E2B2	CD	BD	E0			3940	CALL	AHEX
E2B5	BB					3950	XCHG	
E2B6	E3					3960	XTHL	
E2B7	4E					3970 MLOOP	MOV	C,M ;BACK TO NORMAL
E2B8	E3					3980	XTHL	
E2B9	73					3990	MOV	A,B
E2BA	FF	4D				4000	CPI	'M'
E2BC	28	04				4010	JRZ	NEXCH
E2BE	7E					4020	MOV	A,M
E2BF	E3					4030	XTHL	
E2C0	77					4040	MOV	M,A
E2C1	E3					4050	XTHL	
E2C2	71					4060 NEXCH	MOV	M,C
E2C3	23					4070	INX	H
E2C4	E3					4080	XTHL	
E2C5	CD	3F	E2			4090	CALL	BMP
E2C8	CA	52	E0			4100	JZ	START
E2CB	18	EA				4110	JR	MLOOP
E2CD						4120 * NON DESTRUCTIVE MEMORY TEST		
E2CD	CD	D1	E4			4130 NDMT	CALL	PTSTNG
E2D0	4D	45	4D	20		4140	DTH	'MEM CHECK'
E2D4	43	43	45	43				
E2D3	CB							

Extended Systems Monitor User's Manual

Page 9

Addr	B1	B2	B3	B4	E	Line Label	Opcd	Operand	
E2D9	21	00	00			4150	LXI	H,0	;START AT ZERO
E2DC	4E					4160 NDLOP	MOV	C,M	
E2DD	06	FF				4170	MVI	B,OFFH	
E2DF	70					4180	MOV	M,B	
E2E0	7E					4190	MOV	A,M	
E2E1	B8					4200	CMP	B	
E2E2	C2	EA	E2			4210	JNZ	ERRJP	;PRINT ERROR
E2E5	06	00				4220	MVI	B,0	
E2E7	70					4230	MOV	M,B	
E2E8	7E					4240	MOV	A,M	
E2E9	B8					4250	CMP	B	
E2EA	C2	1D	E2			4260 ERRJP	JNZ	ERR	
E2ED	71					4270	MOV	M,C	
E2EE	23					4280	INX	H	
E2EF	18	EB				4290	JR	NDLOP	
E2F1						4300 * COMPARE TWO BLOCKS OF MEMORY			
E2F1	CD	D1	E4			4310 COMPR	CALL	PTSTNG	
E2F4	43	4F	4D	50		4320	DTH	'COMPARE '	
E2F8	41	52	45	A0					
E2FC	CD	0E	E1			4330	CALL	TAHEX	
E2FF	E5					4340	PUSH	H	
E300	CD	BD	E0			4350	CALL	AHEX	
E303	EB					4360	XCHG		
E304	7E					4370 VMLOP	MOV	A,M	
E305	23					4380	INX	H	
E306	E3					4390	XTHL		
E307	3E					4400	CMP	M	
E308	46					4410	MOV	B,M	
E309	C4	1D	E2			4420	CNZ	ERR	
E30C	CD	3F	E2			4430	CALL	BMP	
E30F	E3					4440	XTHL		
E310	20	F2				4450	JRNZ	VMLOP	
E312	F1					4460	POP	PSW	
E313	C9					4470	RET		
E314						4480 * SEARCH FOR SPECIFIC CODES			
E314	F5					4490 FIND	PUSH	PSW	
E315	CD	D1	E4			4500	CALL	PTSTNG	
E318	46	49	4E	44		4510	DTH	'FIND-2 '	
E31C	2D	32	A0						
E31F	13	0D				4520 SRCHENT	JR	SRCHENT	
E321	F5					4530 SRCH	PUSH	PSW	
E322	CD	D1	E4			4540	CALL	PTSTNG	
E325	53	45	41	52		4550	DTH	'SEARCH-1 '	
E329	43	48	2D	31					
E32D	A0								
E32E	CD	0E	E1			4560 SRCHENT	CALL	TAHEX	
E331	E5					4570	PUSH	H	;SAVE H
E332	CD	0A	E1			4580	CALL	AHE2	;READ 2 DIGITS
E335	E3					4590	XCHG		;H=CODE,D=F
E336	45					4600	MOV	B,L	;PUT CODE IN B
E337	E1					4610	POP	H	;RESTORE H
E338	F1					4620	POP	PSW	
E339	FE	53				4630	CPI	'S'	
E33B	F5					4640	PUSH	PSW	
E33C	28	07				4650	JRZ	CONT	
E33E	E5					4660	PUSH	H	

Extended Systems Monitor User's Manual

Page 10

Addr	B1	B2	B3	B4	E	Line Label	Opcd	Operand	
E33F	CD	0A	E1			4670	CALL	AHE2	;READ 2 DIGITS
E342	EB					4680	XCHG		
E343	4D					4690	MOV	C,L	
E344	E1					4700	POP	H	
E345	7E					4710	CONT	MOV A,M	;READ MEMORY
E346	B8					4720	CMP	B	;COMPARE TO CODE
E347	20	12				4730	JRNZ	SKP	;SKIP IF NO COMP
E349	F1					4740	POP	PSW	;FETCH CONTROL
E34A	FE	53				4750	CPI	'S'	
E34C	F5					4760	PUSH	PSW	
E34D	28	06				4770	JRZ	OBCP	
E34F	23					4780	INX	H	
E350	7E					4790	MOV	A,M	
E351	2B					4800	DCX	H	
E352	B9					4810	CMP	C	
E353	20	06				4820	JRNZ	SKP	
E355	23					4830	OBCP	INX	H
E356	7E					4840	MOV	A,M	;READ NEXT BYTE
E357	2B					4850	DCX	H	;DECR ADDRESS
E358	CD	1D	E2			4860	CALL	ERR	;PRINT CODES
E35B	CD	3F	E2			4870	SKP	CALL	BMP
E35E	20	E5				4880	JRNZ	CONT	;CHECK IF DONE
E360	F1					4890	POP	PSW	;BACK FOR MORE
E361	C9					4900	RET		
E362						4910	*		
E362						4920	*	INPUT DATA FROM A PORT	
E362	CD	D1	E4			4930	PINPT	CALL	PTSTNG
E365	49	4E	50	55		4940		DTH	'INPUT '
E369	54	A0							
E36B	CD	0A	E1			4950	CALL	AHE2	;READ 2 DIGITS
E36E	4B					4960	MOV	C,E	
E36F	ED	78				4970	INP	A	
E371	C3	26	E2			4980	JMP	PT2	
E374						4990	*		
E374						5000	*	OUTPUT TO A PORT	
E374	CD	D1	E4			5010	POUTP	CALL	PTSTNG
E377	4F	55	54	50		5020		DTH	'OUTPUT '
E378	55	54	A0						
E37E	CD	0A	E1			5030	CALL	AHE2	;READ 2 DIGITS
E381	CD	0A	E1			5040	CALL	AHE2	;READ 2 DIGITS
E384	4D					5050	MOV	C,L	
E385	ED	59				5060	OUTP	E	
E387	C9					5070	RET		
E388						5080	*		

Extended Systems Monitor User's Manual

Page 11

Addr	B1	B2	B3	B4	E	Line Label	Opcd	Operand
E388						5090 *		
E388						5100 *****		
E388						5110 *		*
E388						5120 * VIDEO DRIVER FOR FLASHWRITER II		*
E388						5130 *		*
E388						5140 *****		
E388						5145 *		
E388	F000	=				5150 PAGE	EQU	PR+1000H ;SCREEN LOCATION
E388	0020	=				5160 SPACE	EQU	20H
E388	0004	=				5170 CLRSCRN	EQU	4
E388						5180 *		
E388						5190 * COMMANDS:		
E388						5200 * (B) HOME CURSOR		
E388						5210 * (D) CLEAR SCREEN		
E388						5220 * (E) PRINT CONTROL CODE		
E388						5230 * (H) BACKSPACE		
E388						5240 * (I) TAB		
E388						5250 * (J) LINEFEED		
E388						5260 * (M) CARRIAGE RETURN		
E388						5270 * (N) NO CURSOR		
E388						5280 * (P) CLEAR TO END OF SCREEN		
E388						5290 * (Q) CLEAR TO END OF LINE		
E388						5300 * (R) CURSOR DOWN		
E388						5310 * (T) TOGGLE REVERSE VIDEO		
E388						5320 * (U) CURSOR UP		
E388						5330 * (W) CURSOR LEFT		
E388						5340 * (X) CLEAR TO START OF LINE		
E388						5350 * (Z) CURSOR RIGHT		
E388						5360 * ESC XY POSITION LEAD-IN		
E388						5370 *		
E388						5380 * VIDEO BOARD PARAMETERS		
E388	0050	=				5390 HORIZ	EQU	30 ;NO. OF CHARACTER
E388	0018	=				5400 VERT	EQU	24 ;NO. OF LINES
E388						5410 *		
E388	3E 14					5415 TVIDEO	MVI	A,'T'-64 ;TOGGLE VIDEO
E38A						5416 *		
E38A	F5					5420 VIDEO	PUSH	PSW
E38B	C5					5430	PUSH	B
E38C	D5					5440	PUSH	D
E38D	E5					5450	PUSH	H
E38E	B6 7F					5460	ANI	07FH
E390	4F					5470	MOV	C,A
E391	3A 00 E8					5480	LDA	BASE+800H
E394	FE C3					5490	CPI	0C3H ;PROM THERE?
E396	79					5500	MOV	A,C
E397	CC 00 E8					5510	CZ	BASE+800H ;CALL IT IF SO
E39A	CD 6F E4					5520 DISPL	CALL	LIFTCURS ;ERASE CURSOR
E39D	3A EA FF					5530	LDA	XYFLAG
E3A0	A7					5540	ANA	A
E3A1	28 0A					5550	JRZ	NOXY
E3A3	3D					5560	DCR	A
E3A4	32 EA FF					5570	STA	XYFLAG
E3A7	CA BC E4					5580	JZ	YPOS
E3AA	C3 B3 E4					5590	JMP	XPOS
E3AD	79					5600 NOXY	MOV	A,C ;RECOVER CHARACT.
E3AE	FE 20					5610	CPI	SPACE ;PRINTING CODE?

Extended Systems Monitor User's Manual

Page 12

Addr	B1	B2	B3	B4	E	Line Label	Opnd	Operand
E380	F2	E4	E3			5620	JP	PRINT
E3B3	FE	1C				5630	CPI	PCL-TABL ; TOO LARGE?
E3B5	F2	51	E4			5640	JP	RET
E3B8	E5					5650	PUSH	H ; CURSOR IN MEMORY
E3B9	21	C7	E3			5660	LXI	H,TABL ; TABLE START
E3BC	5F					5670	MOV	E,A
E3BD	16	00				5680	MVI	D,0
E3BF	19					5690	DAD	D
E3C0	5E					5700	MOV	E,M
E3C1	21	E3	E3			5710	LXI	H,PCL
E3C4	19					5720	DAD	D
E3C5	E3					5730	XTHL	
E3C6	C9					5740	RET	;RECOVER H ;EXECUTE ROUTINE
E3C7						5750	* CONTROL CHARACTER JUMP TABLE	
E3C7	6E					5760	TABL	DB RET-PCL ;Q
E3C8	6E					5770	DB RET-PCL ;A	
E3C9	63					5780	DB HOME-PCL ;B HOME CURSOR	
E3CA	6E					5790	DB RET-PCL ;C	
E3CB	60					5800	DB FORM-PCL ;D CLEAR SCREEN	
E3CC	00					5810	DB PCL-PCL ;E PRT CONTROL	
E3CD	6E					5820	DB RET-PCL ;F	
E3CE	6E					5830	DB RET-PCL ;G	
E3CF	42					5840	DB DBACKSP-PCL ;H BACKSPACE	
E3D0	59					5850	DB TAB-PCL ;I TAB OVER	
E3D1	12					5860	DB LINF-PCL ;J LINE FEED	
E3D2	6E					5870	DB RET-PCL ;K	
E3D3	6E					5880	DB RET-PCL ;L	
E3D4	6A					5890	DB CRET-PCL ;M CARRIAGE RET	
E3D5	71					5900	DB RET+3-PCL ;N NO CURSOR	
E3D6	6E					5910	DB RET-PCL ;O	
E3D7	A5					5920	DB CLEND-PCL ;P CLR SCN TO END	
E3D8	AA					5930	DB CLLINE-PCL ;Q CLR LINE TO END	
E3D9	12					5940	DB LINF-PCL ;R CURSOR DOWN	
E3DA	6E					5950	DB RET-PCL ;S	
E3DB	76					5960	DB TVIDF-PCL ;T TOGGLE VIDEO	
E3DC	80					5970	DB CURSUP-PCL ;U CURSOR UP	
E3DD	6E					5980	DB RET-PCL ;V	
E3DE	50					5990	DB BACKSP-PCL ;W CURSOR LEFT	
E3DF	E2					6000	DB CLSTRT-PCL ;X CLR START OF L	
E3E0	6E					6010	DB RET-PCL ;Y	
E3E1	06					6020	DB EOL-PCL ;Z CURSOR RIGHT	
E3E2	C9					6030	DB LEDIN-PCL ;[ESC=XY LEADIN	
E3E3						6040	*	
E3E3	48					6050	* PRINT CODE IN B REGARDLESS	
E3E4						6060	PCL MOV C,B	
E3E4	3A DD FF					6070	* PRINT THE CHARACTER ON THE SCREEN	
E3E4	3A DD FF					6080	PRINT LDA VFL	
E3E7	A9					6090	XRA C	
E3E8	77					6100	MOV M,A	
E3E9						6110	* EOL CHECKS THE CURS POS FOR END OF LINE	
E3E9	3A DB FF					6120	EOL LDA CURPOS	
E3EC	3C					6130	INR A	
E3ED	FE 50					6140	CPI HORIZ	
E3EF	38 5D					6150	JRC TABRET	
E3F1	AF					6160	XRA A	
E3F2	32 DB FF					6170	STA CURPOS	

Extended Systems Monitor User's Manual

Page 13

Addr	B1	B2	B3	B4	E	Line Label	Opcd	Operand
E3F5						6180 * MOVE DN 1 LINE		
E3F5	3A	DC	FF			6190 LINF	LDA	LINENO
E3F3	FE	17				6200	CPI	VERT-1
E3FA	20	23				6210	JRNZ	NOSCRRL
E3FC						6220 * SCROLL UP ONE LINE		
E3FC	21	50	00			6230 SCROLL	LXI	H,HORIZ
E3FF	ED	5B	DF	FF		6240	LDED	TOSCN
E403	19					6250	DAD	D
E404	ED	A0				6260 SCRL	LDI	
E406	ED	A0				6270	LDI	
E408	7C					6280	MOV	A,H
E409	FE	F7				6290	CPI	HORIZ*VERT+PAGE/256
E40B	20	F7				6300	JRNZ	SCRL
E40D	7D					6310	MOV	A,L
E40E	FE	80				6320	CPI	HORIZ*VERT+PAGE&OFFH
E410	20	F2				6330	JRNZ	SCRL
E412	3A	DC	FF			6340	LDA	LINENO
E415						6350 * ERASE BOTTOM LINE		
E415	EB					6360 EBOTL	XCHG	
E416	06	50				6370	MVI	B,HORIZ
E418	36	20				6380 ELOP	MVI	M,SPACE
E41A	23					6390	INX	H
E41B	05					6400	DCR	B
E41C	20	FA				6410	JRNZ	ELOP
E41E	3D					6420	DCR	A
E41F	3C					6430 NOSCRRL	INR	A
E420	32	DC	FF			6440	STA	LINENO
E423	18	2C				6450	JR	RET
E425						6460 *		
E425	36	20				6470 * ERASE BEFORE BACKSPACING		
E427	3A	DB	FF			6480 DBACKSP	MVI	M,20H
E42A	A7					6481	LDA	CURPOS
E42B	28	24				6482	ANA	A
E42D	3D					6483	JRZ	RET
E42E	2B					6484	DCR	A
E42F	36	20				6485	DCX	H
E431	13	1B				6486	MVI	M,20H
E433						6487	JR	TABRET
E433	3A	DB	FF			6510 * MOVE THE CURSOR BACK		
E436	3D					6520 BACKSP	LDA	CURPOS
E437	F2	4E	E4			6530	DGR	A
E43A	18	11				6540	JP	TABRET
E43C						6550	JR	CRET
E43C	3A	DB	FF			6560 * TAB OVER TO THE NEXT 3 MULTIPLE		
E43F	F6	07				6570 TAB	LDA	CURPOS
E441	18	A9				6580	ORI	7
E443						6590	JR	EOL+3
E443	CD	9A	E4			6600 * CLEAR THE SCREEN AND HOME UP		
E446	AF					6610 FORM	CALL	CLEAR
E447	32	DC	FF			6620 HOME	XRA	A
E44A	32	DD	FF			6630	STA	LINENO
E44D						6640	STA	VFL ;CLR VID FLAG
E44D	AF					6650 * CARRIAGE RETURN		
E44E	32	DB	FF			6660 CRET	XRA	A
E451						6670 TABRET	STA	CURPOS
						6680 * RETURN TO THE CALLING ROUTINE		

Addr	B1	B2	B3	B4	E	Line Label	Opcd	Operand
E451	CD	6F	E4			6690 RET	CALL	LIFTCURS
E454	E1					6700	POP	H
E455	D1					6710	POP	D
E456	C1					6720	POP	B
E457	F1					6730	POP	PSW
E458	C9					6740	RET	
E459	3A	DD	FF			6750 TVIDF	LDA	VFL
E45C	EE	80				6760	XRI	80H
E45E	32	DD	FF			6770	STA	VFL
E461	18	EE				6780	JR,	RET
E463						6790 *		
E463						6800 * MOVE THE CURSOR UP		
E463	3A	DC	FF			6810 CURSUP	LDA	LINENO
E466	A7					6820	ANA	A
E467	28	E8				6830	JRZ	RET
E469	3D					6840	DCR	A
E46A	32	DC	FF			6850 STORLN	STA	LINENO
E46D	18	E2				6860	JR	RET
E46F						6870 * CALCULATE MEM ADD FROM CURS POS		
E46F	21	B0	EF			6880 LIFTCURS	LXI	H,PAGE-HORIZ
E472	11	50	00			6890	LXI	D,HORIZ
E475	3A	DC	FF			6900	LDA	LINENO
E478	3C					6910	INR	A
E479	19					6920 CLOP	DAD	D
E47A	3D					6930	DCR	A
E47B	20	FC				6940	JRNZ	CLOP
E47D	ED	5B	DB	FF		6950 CFIN	LDED	CURPOS
E481	57					6960	MOV	D,A
E482	19					6970	DAD	D
E483						6980 * REVERSE THE VIDEO		
E483	7E					6990	MOV	A,M
E484	EE	30				7000	XRI	80H
E486	77					7010	MOV	M,A
E487	C9					7020	RET	
E488						7030 * CLEAR TO END OF SCREEN		
E488	CD	A3	E4			7040 CLEND	CALL	WRSPC
E488	18	C4				7050	JR	RET
E48D						7060 * CLEAR TO END OF LINE		
E48D	3A	D3	FF			7070 CLLINE	LDA	CURPOS
E490	36	20				7080	MVI	M,20H
E492	23					7090	INX	H
E493	3C					7100	INR	A
E494	FE	50				7110	CPI	50H
E496	20	F8				7120	JRNZ	CLLINE+3
E493	18	B7				7130	JR	RET
E49A						7140 * CLEAR THE SCREEN		
E49A	21	00	F0			7150 CLEAR	LXI	H,PAGE
E49D	22	DF	FF			7160	SHLD	TOSCN
E4A0	22	EA	FF			7170	SHLD	XYFLAG
E4A3	36	20				7180 WRSPC	MVI	H,20H
E4A5	23					7190	INX	H
E4A6	7C					7200	MOV	A,H
E4A7	FE	F3				7210	CPI	PAGE+2048/256
E4A9	20	F8				7220	JRNZ	WRSPC
E4AB	C9					7230	RET	
E4AC						7240 *		

Extended Systems Monitor User's Manual

Page 15

Addr	B1	B2	B3	B4	E	Line Label	Opcd	Operand
E4AC						7250 * PROCESS LEAD IN CODE		
E4AC	3E	02				7260 LEPIN	MVI	A,2
E4AE	32	EA	FF			7270	STA	XYFLAG
E4B1	18	9E				7230	JR	RET
E4B3						7290 *		
E4B3						7300 * SET X AND Y CURSOR POSITIONS		
E4B3	79					7310 XPOS	MOV	A,C
E4B4	FE	50				7320	CPI	80
E4B6	38	02				7330	JRC	XINRG
E4B8	3E	4F				7340	MVI	A,79
E4BA	18	92				7350 XINRG	JR	TABRET
E4BC						7360 *		
E4BC	79					7370 YPOS	MOV	A,C
E4BD	FE	18				7380	CPI	24
E4BF	38	02				7390	JRC	YINRG
E4C1	3E	17				7400	MVI	A,23
E4C3	18	A5				7410 YINRG	JR	STORLN
E4C5						7420 *		
E4C5	AF					7430 CLSTRT	XRA	A
E4C6	32	DB	FF			7440	STA	CURPOS
E4C9	CD	6F	E4			7450	CALL	LIFTCURS
E4CC	18	BF				7460	JR	CLLINE
E4CE	E4CE	=				7470 MSEND	EQU	\$
E4CE						7480 * CURSOR STORAGE LOCATIONS		
E4CE						7490	ORG	SPTR+0BH
FFDB	00					7500 CURPOS	DB	0
FFDC	00					7510 LINENO	DB	0
FFDD	00					7520 VFL	DB	0
FFDE	00					7530 WIDTH	DB	0
FFDF	00	F0				7540 TOSCN	DW	PAGE
FFE1	00	00				7550 TCURPOS	DW	0
FFE3						0030	LINK	'M5'
FFE3						0000 * ADDITIONS TO 4.0 MONITOR		
FFE3						0010	ORG	MSEND
E4CE						0020 * PRINT A STRING		
E4CE	CD	DF	E0			0021 RPTSTNG	CALL	CRLF
E4D1	E3					0030 PTSTNG	XTHL	;CRLF FIRST
E4D2	7E					0040	MOV	A,M
E4D3	23					0050	INX	H
E4D4	E3					0060	XTHL	
E4D5	A7					0070	ANA	A
E4D6	CD	8A	E3			0080	CALL	VIDEO
E4D9	F8					0090	RM	;PRINT IT
E4DA	18	F5				0100	JR	PTSTNG
E4DC						0110 * SIGN ON MESSAGE		
E4DC	3E	04				0120 SIGN	MVI	A,4
E4DE	CD	8A	E3			0125	CALL	VIDEO
E4E1	21	50	F1			0130	LXI	H,PAGE+150H
E4E4	E5					0140	PUSH	H
E4E5	11	51	F1			0150	LXI	D,PAGE+151H
E4E8	01	30	00			0160	LXI	B,30H
E4EB	36	A0				0170	MVI	H,0AOH
E4ED	ED	B0				0180	LDIR	
E4EF	E1					0190	POP	H
E4F0	11	A0	F1			0200	LXI	D,PAGE+1A0H
E4F3	01	80	02			0210	LXI	B,640

Addr	B1	B2	B3	B4	E	Line Label	Opcd	Operand
E4F6	ED	80				0220	LDIR	
E4F8	CD	D1	E4			0270	CALL	PTSTNG
E4FB	1B					0272	DB	27 ;ESC
E4FC	20	07				0274	DD	2007H ;X=32 Y=7
E4FE	20	56	45	43		0280	DT	' VECTOR GRAPHIC '
E502	54	4F	52	20				
E506	47	52	41	50				
E50A	43	49	43	20				
E50E	1B					0290	DB	27 ;ESC
E50F	20	08				0300	DD	2008H ;X=32 Y=8
E511	20	20	20	20		0310	DT	' MONITOR '
E515	4D	4F	4E	49				
E519	54	4F	52	20				
E51D	20	20	20	20				
E521	1B					0320	DB	27 ;ESC
E522	20	09				0330	DD	2009H ;X=32 Y=9
E524	20	20	56	45		0340	DT	' VERSION 4.0 '
E528	52	53	49	4F				
E52C	4E	20	34	2E				
E530	30	20	20	20				
E534	1B					0350	DB	27 ;ESC
E535	00	8D				0360	DD	8DH ;X=0 Y=13
E537	C9					0380	RET	
E538	CD	CE	E4			0390	PROMPT	CALL RPTSTNG
E53B	4D	6F	6E	3E		0410	DTH	'Mon> '
E53F	A0							
E540	21	00	F0			0420	LXI	H,PAGE
E543	22	DF	FF			0430	SHLD	TOSCN ;FULL SCROLL
E546	C9					0440	RET	
E547						0450	*	
E547						0460	*WIDE ASCII DUMP	
E547	CD	D1	E4			0470	WASCII	CALL PTSTNG
E54A	41	53	43	49		0480	DTH	'ASCII DUMP '
E54E	49	20	44	55				
E552	4D	50	A0					
E553	CD	0E	E1			0490	CALL	TAHEX
E553	CD	9B	E5			0500	CALL	HOMEC
E55B						0510	* MAKE A RULER FOR ASCII DUMP	
E55B	78					0520	RULELP	MOV A,B
E55C	FE	40				0530		CPI 64
E55E	28	1A				0540	JRZ	TERMLIN
E560	E6	0F				0550	ANI	OFH
E562	28	10				0560	JRZ	NUMBER
E564	E6	03				0570	ANI	3
E566	23	03				0580	JRZ	MARKER
E568	3E	20				0590	MVI	A,' '
E56A	CD	8A	E3			0600	REENTR	CALL VIDEO
E56D	04					0610	INR	B
E56E	18	E3				0620	JR	RULELP
E570	3E	6C				0630	MARKER	MVI A,'1'
E572	18	F6				0640	JR	REENTR
E574	73					0650	NUMBER	MOV A,B
E575	CD	2D	E2			0660		CALL BINH
E578	18	F3				0670	JR	REENTR+3
E57A	CD	88	E3			0680	* TOGGLE REVERSE VIDEO	
E57A	CD	88	E3			0690	TERMLIN	CALL TVIDEO

Extended Systems Monitor User's Manual

Page 17

Addr	B1	B2	B3	B4	E	Line	Label	Opcd	Operand
E57D	CD	07	E6			0710	WDMP1	CALL	SETSCRLL
E580	CD	0F	E2			0720		CALL	PTAD
E583	OE	3F				0730		MVI	C,63
E585	CD	8C	E5			0740		CALL	WDMP2
E588	FA	7D	E5			0750		JM	WDMP1
E58B	C8					0760		RZ	
E58C	7E					0770	WDMP2	MOV	A,M
E58D	47					0780		MOV	B,A
E58E	3E	05				0790		MVI	A,'E'-64
E590	CD	8A	E3			0800		CALL	VIDEO
E593	CD	3F	E2			0810		CALL	BMP
E596	C8					0820		RZ	
E597	0D					0830		DCR	C
E593	F8					0840		RM	
E599	18	F1				0850		JR	WDMP2
E598						0860	* HOME CURSOR,	PRINT	"ADDR"
E598	CD	CE	E4			0870	HOME C	CALL	RPTSTNG
E59E	14					0890		DB	'T'-64
E59F	41	44	44	52		0900		DTH	'ADDR'
E5A3	A0								
E5A4	06	00				0910		MVI	B,0
E5A6	3E	18				0920		MVI	A,24
E5A8	32	DE	FF			0930		STA	WIDTH
E5AB	C9					0940		RET	
E5AC						0950	* MAKE A RULER	FOR	HEX DUMP
E5AC	78					0960	HEXRULER	MOV	A,B
E5AD	FE	10				0970		CPI	16
E5AF	28	06				0980		JRZ	HEXRCT
E5B1	CD	2F	E7			0990		CALL	PT2S
E5B4	04					1000		INR	B
E5B5	18	F5				1010		JR	HEXRULER
E5B7						1020	* EXTEND FOR ASCII		
E5B7	CD	DA	E0			1030	HEXRCT	CALL	SPCE
E5BA	CD	DA	E0			1040		CALL	SPCE
E5BD	06	00				1050		MVI	B,0
E5BF	78					1060	HEXRLP	MOV	A,B
E5C0	FE	10				1070		CPI	16
E5C2	C8					1080		RZ	
E5C3	E6	0F				1090		ANI	OFH
E5C5	CD	31	E2			1100		CALL	BINL
E5C8	04					1110		INR	B
E5C9	18	F4				1120		JR	HEXRLP
E5CB						1130	* HEX DUMP ROUTINE		
E5CB	CD	D1	E4			1140	HEXRUL	CALL	RPTSTNG
E5CE	48	45	53	20		1150		DTH	'HEX DUMP'
E5D2	44	55	4D	50					
E5D6	A0								
E5D7	CD	0E	E1			1160		CALL	TAHEX
E5DA	CD	98	E5			1170		CALL	HOME C
E5DD	CD	AC	E5			1180		CALL	HEXRULER
E5E0	CD	38	E3			1200		CALL	TVIDEO
E5E3	CD	07	E6			1210		CALL	SETSCRLL
E5E6	CD	0F	E2			1220	HLP1	CALL	PTAD
E5E9	E5					1230		PUSH	H
E5EA	D5					1240		PUSH	D
E5EB	OE	10				1250		MVI	C,16

Extended Systems Monitor User's Manual

Page 18

Addr	B1	B2	B3	B4	E	Line Label	Opcd	Operand
E5ED	7E					1260 HLP2	MOV	A,H
E5EE	CD	2F	E7			1270	CALL	PT2S
E5F1	23					1280	INX	H
E5F2	0D					1290	DCR	C
E5F3	C2	ED	E5			1300	JNZ	HLP2
E5F6	D1					1310	POP	D
E5F7	E1					1320	POP	H
E5F8	0E	0F				1330	MVI	C,15
E5FA	CD	DA	E0			1340	CALL	SPCE
E5FD	CD	DA	E0			1350	CALL	SPCE
E600	CD	8C	E5			1360	CALL	WDMP2
E603	FA	E3	E5			1370	JM	HLP1-3
E605	C9					1380	RET	
E607						1390 * CHECK TO SET SCROLL POINT		
E607	3A	DE	FF			1400 SETSCRLL	LDA	WIDTH
E60A	3D					1410	DCR	A
E60B	32	DE	FF			1420	STA	WIDTH
E60E	20	07				1430	JRNZ	CTSCRL
E610	01	50	F0			1440	LXI	B,PAGE+50H ;2ND LINE
E613	ED	43	DF	FF		1450	SBCD	TOSCN ;SCROLL POINT
E617	C9					1460 CTSCRL	RET	
E618						1470 *		
E618						1480 * PROGRAM MEMORY		
E618	CD	D1	E4			1490 PROGRAM	CALL	PTSTNG
E618	50	52	4F	47		1500	DTH	'PROGRAM'
E61F	52	41	4D	A0				
E623	CD	BD	E0			1510	CALL	AHEX ;ADDR IN HL
E626	ED	53	E1	FF		1520	SDED	TCURPOS
E62A	CD	9B	E5			1530	CALL	HOME C ;PRINT "ADDR"
E62D	CD	AC	E5			1540	CALL	HEXRULER
E630	CD	88	E3			1560	CALL	TVIDEO
E633	AF					1570	XRA	A
E634	32	DE	FF			1580	STA	WIDTH
E637	CD	A1	E6			1590	CALL	PRT1LINE ;PRINT LINE CONT
E63A	CD	2F	E1			1600 POLLOOP	CALL	ESCAPE
E63D	CD	ED	E0			1610	CALL	HEX
E640	2A	E1	FF			1620	LHLD	TCURPOS
E643	30	1A				1630	JRNC	MODMEM
E645						1640 * CONTROL CODE TABLE		
E645	FE	20				1650	CPI	' '
E647	23	46				1660	JRZ	CSRT
E649	FE	03				1670	CPI	8
E64B	28	45				1680	JRZ	CSLT
E64D	FE	12				1690	CPI	'R'-64
E64F	28	39				1700	JRZ	CSDN
E651	FE	15				1710	CPI	'U'-64
E653	28	2F				1720	JRZ	CSUP
E655	FE	17				1730	CPI	'W'-64
E657	28	39				1740	JRZ	CSLT
E659	FE	1A				1750	CPI	'Z'-64
E65B	28	32				1760	JRZ	CSRT
E65D	18	DB				1770	JR	POLLOOP
E65F						1780 * MODIFY A MEMORY LOCATION		
E65F	2A	E1	FF			1790 MODMEM	LHLD	TCURPOS
E662	4F					1800	MOV	C,A
E663	3A	DE	FF			1810	LDA	WIDTH

Extended Systems Monitor User's Manual

Page 19

Addr	B1	B2	B3	B4	S	Line Label	Opnd	Operand
E666	A7					1820	ANA	A
E667	7E					1830	MOV	A,M
E668	28	0D				1840	JRZ	LSNIBL
E66A	E6	F0				1850	ANI	OF0H
E66C	B1					1860	ORA	C
E66D	77					1870 REMEM	MOV	M,A
E66E	3A	DE	FF			1880	LDA	WIDTH
E671	EE	01				1890	XRI	1
E673	20	1F				1900	JRNZ	RTRTN+1
E675	18	18				1910	JR	CSRT
E677	17					1920 LSNIBL	RAE	
E678	17					1930	RAL	
E679	17					1940	RAL	
E67A	17					1950	RAL	
E67B	E6	F0				1960	ANI	OF0H
E67D	B1					1970	ORA	C
E67E	0F					1980	RRC	
E67F	0F					1990	RRC	
E680	0F					2000	RRC	
E681	0F					2010	RRC	
E682	18	E9				2020	JR	REMEM
E684						2030 * MOVE UP ONE LINE		
E684	11	F0	FF			2040 CSUP	LXI	D,-16
E687	19					2050	DAD	D
E633	18	09				2060	JR	RTRTN
E68A						2070 * MOVE DOWN ONE LINE		
E68A	11	10	00			2080 CSDN	LXI	D,16
E68D	18	F8				2090	JR	CSUP+3
E68F						2100 * MOVE RIGHT ONE SPACE		
E68F	23					2110 CSRT	INX	H
E690	13	01				2120	JR	RTRTN
E692	2B					2130 * MOVE LEFT ONE SPACE		
E692						2140 CSLT	DCX	H
E693						2150 *		
E693	AF					2160 RTRTN	XRA	A
E694	32	DE	FF			2170	STA	WIDTH
E697	22	E1	FF			2180	SHLD	TCURPOS
E69A	3E	15				2190 UPAROW	MVI	A,'U'-64
E69C	CD	8A	E3			2200	CALL	VIDEO
E69F	18	96				2210	JR	POLLOOP-3
E6A1						2220 * PRINT A LINE CONTAINING ((H))		
E6A1	2A	E1	FF			2230 PRT1LINE	LHLD	TCURPOS
E6A4	E5					2240	PUSH	H
E6A5	D1					2250	POP	D
E6A6	7D					2260	MOV	A,L
E6A7	F6	0F				2270	ORI	OFH
E6A9	5F					2280	MOV	E,A
E6AA	E6	F0				2290	ANI	OF0H
E6AC	6F					2300	MOV	L,A
E6AD	CD	E6	E5			2310	CALL	HLP1
E6B0						2320 * NOW PUT CURSOR WHERE IT GOES		
E6B0	CD	6F	E4			2330	CALL	LIFTCURS
E6B3	2A	E1	FF			2340	LHLD	TCURPOS
E6B6	7D					2350	MOV	A,L
E6B7	E6	0F				2360	ANI	OFH
E6B9	6F					2370	MOV	L,A

Extended Systems Monitor User's Manual

Page 20

Addr	B1	B2	B3	B4	S	Line	Label	Opcd	Operand
E6BA	3E	05				2380		MVI	A,5
E6BC	2D					2390	PLOP1	DCR	L
E6BD	FA	C4	E6			2400		JM	PGCONT
E6C0	C6	03				2410		ADI	3
E6C2	18	F8				2420		JR	PLOP1
E6C4	6F					2430	PGCONT	MOV	L,A
E6C5	3A	DE	FF			2440		LDA	WIDTH
E6C8	85					2450		ADD	L
E6C9						2460	* A = 5+3*L+W		
E6C9	32	DB	FF			2470		STA	CURPOS
E6CC	C3	6F	E4			2480		JMP	LIFTCURS
E6CF						2490	*		
E6CF						2500	*		
E6CF						2510	* DISPLAY REGISTERS		
E6CF	CD	D1	E4			2520	DREGS	CALL	PTSTNG
E6D2	52	45	47	49		2530		DTH	'REGISTERS'
E6D6	53	54	45	52					
E6DA	D3								
E6DB						2540	* DUMP REGISTERS AFTER ENTRY FROM RST 7		
E6DB	E3					2550	DUMPREGS	XTHL	
E6DC	F5					2560		PUSH	PSW
E6DD	CD	35	E7			2570		CALL	DISPREGS
E6E0	2B					2580		DCX	H
E6E1	CD	0F	E2			2590		CALL	PTAD
E6E4	E1					2600		POP	H
E6E5	C5					2610		PUSH	B
E6E6	CD	8A	E7			2620		CALL	PRTFLGS
E6E9	C1					2630		POP	B
E6EA	CD	12	E2			2640		CALL	PTAD+3
E6ED	E1					2650		POP	H
E6EE	22	E3	FF			2660		SHLD	HLTEMP
E6F1	CD	AB	E7			2670		CALL	PTHREE
E6F4	DD	E5				2680		PUSH	IX
E6F6	E1					2690		POP	H
E6F7	CD	12	E2			2700		CALL	PTAD+3
E6FA	FD	E5				2710		PUSH	IY
E6FC	E1					2720		POP	H
E6FD	CD	12	E2			2730		CALL	PTAD+3
E700	21	00	00			2740		LXI	H,0
E703	39					2750		DAD	SP
E704	22	E5	FF			2760		SHLD	SPTEMP
E707	CD	12	E2			2770		CALL	PTAD+3
E70A	08					2780		EXAF	
E70B	F5					2790		PUSH	PSW
E70C	E1					2800		POP	H
E70D	CD	12	E2			2810		CALL	PTAD+3
E710	D9					2820		EXX	
E711	CD	AB	E7			2830		CALL	PTHREE
E714	D9					2840		EXX	
E715	0A					2850		LDAX	B
E716	CD	2F	E7			2860		CALL	PT2S
E719	1A					2870		LDAX	D
E71A	CD	2F	E7			2880		CALL	PT2S
E71D	2A	E3	FF			2890		LHLD	HLTEMP
E720	7E					2900		MOV	A,M
E721	CD	2F	E7			2910		CALL	PT2S

Extended Systems Monitor User's Manual

Page 21

Addr	B1	B2	B3	B4	E	Line	Label	Opcd	Operand
E724	2A	E5	FF			2920		LHLD	SPTEMP
E727	F9					2930		SPHL	
E728	E1					2940		POP	H
E729	CD	12	E2			2950		CALL	PTAD+3
E72C	C3	46	E0			2960		JMP	CLRBRK ;CLEAR BREAKPOINT
E72F				*		2970			
E72F	CD	26	E2			2980	PT2S	CALL	PT2 ;PRINT 2 CHARS
E732	C3	DA	E0			2990		JMP	SPCE ;PRINT SPACE
E735						3000	* DISPLAY REGISTER HEADER ON SCREEN		
E735	CD	CE	E4			3010	DISPREGS	CALL	RPTSTNG
E738	14					3020		DB	'T'-64
E739	41	44	44	52		3040		DT	'ADDR FLAGS AF BC DE'
E73D	20	46	4C	41					
E741	47	53	20	20					
E745	41	46	20	20					
E749	20	42	43	20					
E74D	20	20	44	45					
E751	20	20	20	48		3050		DT	' HL IX IY SP '
E755	4C	20	20	20					
E759	49	53	20	20					
E75D	20	49	59	20					
E761	20	20	53	50					
E765	20								
E766	20	20	41	46		3060		DT	' AF '
E76A	27					3070		DB	27H ;
E76B	20	20	42	43		3080		DT	' BC '
E76F	27					3090		DB	27H
E770	20	20	44	45		3100		DT	' DE '
E774	27					3110		DB	27H
E775	20	20	48	4C		3120		DT	' HL '
E779	27					3130		DB	27H
E77A	20	40	42	20		3140		DT	' @B @D @H @SP '
E77E	40	44	20	40					
E782	48	20	40	53					
E786	50	20							
E788	94					3150		DB	'T'+64
E789	C9					3160		RET	
E78A				*		3170			
E78A				*		3180	* PRINT FLAGS		
E78A	01	5A	40			3190	PRTFLGS	LXI	B,405AH ;Z
E78D	CD	BA	E7			3200		CALL	MASKFLG
E790	01	43	01			3210		LXI	B,143H ;C
E793	CD	BA	E7			3220		CALL	MASKFLG
E796	01	4D	80			3230		LXI	B,804DH ;M
E799	CD	BA	E7			3240		CALL	MASKFLG
E79C	01	45	04			3250		LXI	B,445H ;E
E79F	CD	BA	E7			3260		CALL	MASKFLG
E7A2	01	48	10			3270		LXI	B,1043H ;H
E7A5	CD	BA	E7			3280		CALL	MASKFLG
E7A8	C3	DA	E0			3290		JMP	SPCE
E7AB				*		3300			
E7AB				*		3310	* PRINT BC DE HL IN ORDER		
E7AB	E5					3320	PTHREE	PUSH	H
E7AC	C5					3330		PUSH	B
E7AD	E1					3340		POP	H
E7AE	CD	12	E2			3350		CALL	PTAD+3

Extended Systems Monitor User's Manual

Page 22

Address	B1	B2	B3	B4	B5	Line Label	Opnd	Operands
E7B1	D5					3360	PUSH	D
E7B2	E1					3370	POP	H
E7B3	CD	12	E2			3380	CALL	PTAD+3
E7B6	E1					3390	POP	H
E7B7	C3	12	E2			3400	JMP	PTAD+3
E7BA						3410 *		
E7BA	7D					3420 MASKFLG	MOV	A,L
E7BB	A0					3430	ANA	B
E7BC	3E	20				3440	MVI	A,20H
E7BD	CA	3A	E3			3450	JZ	VIDEO
E7C1	79					3460	MOV	A,C
E7C2	C3	3A	E3			3470	JMP	VIDEO
E7C5						3480 *		
E7C5						3490 * SET BREAKPOINT		
E7C5	CD	D1	E4			3500 SETBRK	CALL	PTSTNG
E7C8	42	52	45	41		3510	OTH	'BREAK AT '
E7C9	48	20	41	54				
E7D0	A0							
E7D1	CD	3D	E0			3520	CALL	AHEX
E7D4	1A					3530	LDAX	D
E7D5	32	E9	FF			3540	STA	BRKCODE
E7D6	ED	53	E7	FF		3550	SPED	BKPTLOC
E7D8	3E	FF				3560	MVI	A,OFFH ;RST 7
E7DE	12					3570	STAX	D
E7DF	C9					3580	RET	
E7E0						3590 *		
E7E0						3600 * EXTERNAL COMMUNICATIONS		
E7E0	CD	D1	E4			3610 EXTCOM	CALL	PTSTNG
E7E3	46	53	54	20		3620	OTH	'EXT COM '
E7E7	43	4F	4D	A0				
E7EB	DB	05				3630 RECEIVE	IN	B
E7ED	DB	02				3640	ANI	2
E7EF	23	05				3650	JRZ	NEXCHR
E7F1	DB	04				3660	IN	4
E7F3	CD	3A	E3			3670	CALL	VIDEO
E7F6	CD	2F	E1			3680 NEXCHR	CALL	ESCAPE
E7F9	28	60				3690	JRZ	RECEIVE
E7FB	D3	04				3700	OUT	4
E7FD	18	E0				3710	JR	RECEIVE
E7FF						3720 *		
E7FF						3730 * TEMPORARY STORAGE LOCATIONS FOR REGISTERS, ETC.		
FFE3	00	00				3740 ORG	TCURPOS+2	
FFE5	00	00				3750 HLTEMP	DW	0
FFE7	E9	FF				3760 SPTEMP	DW	0
FFE9	00					3770 BKPTLOC	DW	BRKCODE ;BREAKPT LOCATION
FFE9	00					3780 BRKCODE	DB	0 ;CODE AT BREAKPT
FFE9	00					3790 XYFLAG	DB	0 ;CURSOR XY FLAG



